mail@thewaymembranes.com
www.thewaymembranes.com
Chennai, India

TW-0.9-FS

Flat-sheet MBR element, 0.9 m² · Datasheet

Flat-sheet MBR element, 0.9 m². Theway builds it to the published dimensions and connections of the equipment named under "Theway equivalent of", so it fits the installed system with no change to the tank, frame or piping. Main figures: membrane area 0.9 m²; dimensions 515 × 1,059 × 13.5 mm; membrane PVDF, 0.08 µm.



3D render



Dimensions in mm. Drawing not to scale.

Element

Type	Submerged flat sheet, outside-in
Membrane	PVDF on PET non-woven, 0.08 µm
Support panel	ABS
Membrane area	0.9 m²
Dimensions (W × L × T)	515 × 1,059 × 13.5 mm
Permeate nozzle	1, top
Gasket	EPDM

Operating limits *

Operating temperature	5 to 40 °C
Operating pH	5 to 10 (outside cleaning)
MLSS	Not higher than 18,000 mg/L
Transmembrane pressure	Not higher than 20 kPa
Cleaning, organic	Sodium hypochlorite
Cleaning, inorganic	Oxalic or citric acid

* Limits of the equipment this product is built to fit. A project design may set more conservative values.

TMR090 modules the element fits

Module	Elements	m²	W mm	L mm	H mm
TMR090-050S	50	45	730	990	1,470
TMR090-100S	100	90	730	1,720	1,470

Theway equivalent of

Toray Membray TSP-50100	TMR090 modules

Brand and model names belong to their owners and are used only to identify the equipment this product is built to fit. Theway Membranes is not connected with those owners. Check dimensions, connections and operating conditions against the installed equipment before replacing it.

Operating guidelines

- Screen the feed ahead of the membrane tank as for the original installation; hair and fibres shorten membrane life.
- Run air scouring whenever the membranes filter. Stop filtration if the air supply fails.
- Keep transmembrane pressure within the stated limit. A rising TMP calls for cleaning, not for more suction.
- Clean in place with sodium hypochlorite (organic) and citric or oxalic acid (inorganic), within the stated pH, temperature and chlorine limits.
- Keep modules wet once wetted, unless the sheet says they are supplied and stored dry.

General notes

- Before the first order, one installed module is checked against this sheet: header fixing, nozzle or spigot, and edge profile.
- Supplied clean and dry.
- Theway standard limited warranty applies within the stated limits. Operation outside them voids the warranty.

© 2026 Theway Membranes · Document TWM-DS-TW-0-9-FS · Version 1.0 · Released November 2026

mail@thewaymembranes.com
www.thewaymembranes.com
Chennai, India

Legal notice

Guidance only. Values are typical and indicative, given in good faith under the stated reference conditions. They are not guaranteed values and not a warranty of performance; actual performance depends on feed water, pretreatment, design, operation and maintenance.

Binding terms. The only binding specification is Theway's written quotation and order acknowledgement. Supply is under Theway's Terms of Sale, which set out the warranty and limit Theway's liability. Except as stated there, Theway gives no warranty, express or implied, including merchantability or fitness for a particular purpose.

No liability for reliance. To the fullest extent permitted by law, Theway accepts no liability for any loss, damage, injury or cost arising from use of or reliance on this datasheet, or from misuse, incorrect installation, modification or use outside the stated limits, and no liability for indirect, incidental, special or consequential loss.

Your responsibility. The user must confirm that the product is suitable and safe for the intended use, including chemical compatibility, potable-water or food-contact requirements and local regulations, and must have it installed and operated by competent persons.

Equivalents and trade marks. "Equivalent" means built by Theway to fit and operate in place of the named equipment, by its published dimensions, connections and ratings. The product is not made, approved or endorsed by the owner of the named equipment, and Theway is not connected with that owner. Fitting it may affect a warranty or service agreement with the original supplier; check before replacing. Brand and model names belong to their owners and are used only for identification.

Changes and versions. Theway may change designs and specifications without notice. This version supersedes all earlier versions; ask for the current version before ordering.

Ownership. © 2026 Theway Membranes. All rights reserved. This datasheet, its drawings and renderings are Theway's property and are for illustration; supplied products may differ in finish and labelling. They may not be copied, altered, published or passed to third parties without Theway's written permission, except to evaluate Theway products.

Law. Governing law and jurisdiction are as stated in the Terms of Sale. Full terms: www.thewaymembranes.com/post/terms-of-sale and /post/product-and-datasheet-disclaimer.