

mail@thewaymembranes.com
www.thewaymembranes.com
Chennai, India

Tubeflux T12-3030 SS

Sanitary tubular UF module, 12.7 mm · Datasheet

Sanitary tubular ultrafiltration module, Tubeflux series. 3.0-inch (76 mm) SS316L shell, 3,048 mm long, holding 12.7 mm PVDF tubes potted at both ends. Wide channels and a cleanable stainless steel shell make it the module of choice for juice clarification and other food, beverage and dairy streams.





End view: 76 mm shell

Module

Configuration	Multi-tubular, inside-out cross-flow
Tube inside diameter	12.7 mm
Membrane	PVDF, 100 kDa
Shell	SS316L, 76 mm (3.0-inch) outside diameter
Module length (A)	3,048 mm

Operating limits *

Typical operating pressure	4.0 to 5.0 bar
Maximum operating pressure	6.0 bar
Minimum outlet pressure	0.7 bar
Maximum permeate pressure	0.2 bar
Pressure drop per module	0.27 to 0.40 bar
Maximum temperature	60 °C
Maximum cleaning temperature	40 °C
pH, continuous at 25 °C	2 to 10
pH, cleaning at 40 °C	2 to 12
Chlorine for cleaning	Up to 500 ppm; 200 ppm typical
Chlorine exposure, cumulative	250,000 ppm·h

* General-use limits. A project design may set more conservative values for the best performance and the longest service life.

Comparable to

Koch	SUPER-COR 3010 (12.7 mm tubes, 3-inch, 10 ft)

Brand and model names belong to their owners and are used only to identify comparable equipment. Check dimensions, connections and operating conditions against the installed equipment before replacing it.

Operating guidelines

- Start up gradually: raise feed pressure and cross-flow over 30 to 60 seconds, and avoid pressure shocks during start-up, shutdown and cleaning.
- Never let permeate pressure exceed feed pressure. Avoid static back-pressure on the permeate side.
- Clean when permeate flow falls by 10 to 15 % or pressure drop rises by 15 %, using cleaners compatible with the stated pH and temperature limits.
- Complete pretreatment, piping flush and instrument checks before the first start-up.

General notes

- Supplied end-capped and crated. Keep the membrane wet once it has been wetted.
- Theway standard limited warranty applies. Operation outside the stated limits voids the warranty; the user is responsible for the effects of incompatible chemicals.

Theway Membranes believes the information here to be accurate and offers it in good faith. Conditions of use are outside our control, and the user is responsible for checking that the product suits the application. This datasheet is not a contract specification; the order acknowledgement and drawings issued with it govern.

Theway Membranes · 29 Yadaval Street, SIDCO Industrial Estate, Ambattur, Chennai 600 098, India
mail@thewaymembranes.com · +91 44 48502060 · www.thewaymembranes.com

Designs are the property of Theway Membranes. Specifications may change without notice. Drawings are not to scale. Issued November 2026.

mail@thewaymembranes.com
www.thewaymembranes.com
Chennai, India

Important information

Tubeflux T12-3030-SS tubular module datasheet. Read with every page of this document.

DOCUMENT	VERSION	RELEASED	PAGES	ISSUED BY
TWM-DS-TUBEFLUX-T12-3030-SS	**1.1**	**November 2026**	**2**	**Theway Membranes**

Legal notice

Guidance only. Values are typical and indicative, given in good faith under the stated reference conditions. They are not guaranteed values and not a warranty of performance; actual performance depends on feed water, pretreatment, design, operation and maintenance.

Binding terms. The only binding specification is Theway's written quotation and order acknowledgement. Supply is under Theway's Terms of Sale, which set out the warranty and limit Theway's liability. Except as stated there, Theway gives no warranty, express or implied, including merchantability or fitness for a particular purpose.

No liability for reliance. To the fullest extent permitted by law, Theway accepts no liability for any loss, damage, injury or cost arising from use of or reliance on this document, or from misuse, incorrect installation, modification or use outside the stated limits, and no liability for indirect, incidental, special or consequential loss.

Your responsibility. The user must confirm that the product is suitable and safe for the intended use, including chemical compatibility, potable-water or food-contact requirements and local regulations, and must have it installed and operated by competent persons.

Replacement products and trade marks. Where this document names another maker's product, the Theway product is built to fit and operate in its place by its published dimensions, connections and ratings. It is not made, approved or endorsed by that maker, and Theway is not connected with it. Fitting it may affect a warranty or service agreement with the original supplier; check before replacing. Brand and model names belong to their owners and are used only for identification.

Changes and versions. Theway may change designs and specifications without notice. This version supersedes all earlier versions; ask for the current version before ordering.

Ownership. © 2026 Theway Membranes. All rights reserved. This document, its drawings and images are Theway's property and are for illustration; supplied products may differ in finish and labelling. They may not be copied, altered, published or passed to third parties without Theway's written permission, except to evaluate Theway products.

Law. Governing law and jurisdiction are as stated in the Terms of Sale. Full terms: www.thewaymembranes.com/post/terms-of-sale and www.thewaymembranes.com/post/product-and-datasheet-disclaimer.

Questions about this document: mail@thewaymembranes.com · +91 44 48502060 · +91 73974 98660. Always ask for the current version before ordering or designing.