

mail@thewaymembranes.com
www.thewaymembranes.com
Chennai, India

Armaflux 80-1000-SP

8-inch RO pressure vessel, 1,000 psi, side port · Datasheet

FRP pressure vessel for 8-inch spiral-wound RO elements, Armaflux series. Design pressure 1,000 psi (69.0 bar), side entry, for 1 to 7 elements of 40-inch length. Duplex stainless steel side ports on flat sealing faces, with two-port or multiport heads in 1.5, 2 or 2.5-inch grooved sizes. For seawater, high brackish water and brine concentration.





End view: Ø 220 mm shell
Ø 272 mm bell

Rating

Design (maximum operating) pressure	1,000 psi (69.0 bar)
Factory hydrostatic test	1,100 psi (75.9 bar), 1.1 × design; 1.5 × when specified
Operating temperature	−7 to 65 °C
pH, continuous	3 to 11
pH, cleaning, under 30 minutes	2 to 12
Design basis	ASME Boiler and Pressure Vessel Code, Section X

Dimensions and connections

Elements	1 to 7 × 8 in × 40 in
Shell outside diameter	220 ± 2 mm
Shell inside diameter	202.2 ± 0.1 mm
Bell (head) diameter	272 ± 2 mm
Feed and concentrate	Grooved side ports, 1.5 in (2 ports); 1.5, 2 or 2.5 in (multiport)
Permeate	1-inch BSP female, both ends
Side ports	Duplex stainless steel, CD3MN
Port washer, retaining ring	SS316

Materials

Shell	Filament-wound epoxy/glass composite; head-locking grooves wound in, not machined
Bearing plate	Aluminium alloy, hard anodised
Sealing plate, port nut, thrust ring, adapter	Engineering thermoplastic
O-rings and seals	EPDM

Materials (continued)

Saddles	Engineering thermoplastic
Straps	SS304 with cushion
Exterior	White high-gloss polyurethane, RAL 9003

* General-use limits. A project design may set more conservative values for the best performance and the longest service life.

Armaflux 80-1000-SP lengths

Model	Elements	L, overall	P, port to port	S, recommended span	Weight, approx.
80-1000-SP-1	1	1,588 mm	1,194 mm	676	52 kg
80-1000-SP-2	2	2,604 mm	2,210 mm	1,656	67 kg
80-1000-SP-3	3	3,620 mm	3,226 mm	2,674	82 kg
80-1000-SP-4	4	4,637 mm	4,242 mm	1,845 × 2	97 kg
80-1000-SP-5	5	5,653 mm	5,258 mm	2,355 × 2	112 kg
80-1000-SP-6	6	6,669 mm	6,274 mm	2,865 × 2	127 kg
80-1000-SP-7	7	7,685 mm	7,290 mm	3,300 × 2	142 kg

Theway Membranes · 29 Yadaval Street, SIDCO Industrial Estate, Ambattur, Chennai 600 098, India
mail@thewaymembranes.com · +91 44 48502060 · www.thewaymembranes.com
Designs are the property of Theway Membranes. Specifications may change without notice. Drawings are not to scale. Issued November 2026.

mail@thewaymembranes.com
www.thewaymembranes.com
Chennai, India

Installation and operation

• Mount the vessel centred on level supports at the span in the table, with the saddles and straps supplied. Tighten straps lightly; the shell must be free to grow under pressure.

• Connect feed, concentrate and permeate with flexible grooved couplings or hoses. Do not hang manifolds or valves from the vessel ports.

• Tighten the permeate port by hand, then no more than one further turn.

• Fit overpressure protection set at no more than 105 % of the design pressure. The vessel is not for vacuum service.

• Release all pressure before opening a head. Check that each retaining ring is fully seated before start-up.

• Flush with permeate before a long shutdown, and inspect heads and seals at every element change.

General notes

• Each vessel is supplied with heads, seals, element adapters and thrust ring for the element specified, plus two saddles and two straps (three for 4-element and longer vessels).

• Permeate side of the head is rated for 125 psi (8.6 bar) internal pressure. Design pressure applies at the maximum operating temperature.

• State with the order: model, number of elements, element make and model, and port configuration.

• Weights are for the multiport configuration and vary with the port arrangement.

• Theway standard limited warranty applies to vessels used within the stated pressure, temperature and pH limits and installed as described here.

Theway Membranes believes the information here to be accurate and offers it in good faith. Conditions of use are outside our control, and the user is responsible for checking that the product suits the application. This datasheet is not a contract specification; the order acknowledgement and drawings issued with it govern.

Theway Membranes · 29 Yadaval Street, SIDCO Industrial Estate, Ambattur, Chennai 600 098, India
mail@thewaymembranes.com · +91 44 48502060 · www.thewaymembranes.com

Designs are the property of Theway Membranes. Specifications may change without notice. Drawings are not to scale. Issued November 2026.

mail@thewaymembranes.com
www.thewaymembranes.com
Chennai, India

Important information

Armaflux 80-1000-SP RO pressure vessel datasheet. Read with every page of this document.

DOCUMENT	VERSION	RELEASED	PAGES	ISSUED BY
TWM-DS-ARMAFLUX-80-1000-SP	**1.0**	**November 2026**	**3**	**Theway Membranes**

Legal notice

Guidance only. Values are typical and indicative, given in good faith under the stated reference conditions. They are not guaranteed values and not a warranty of performance; actual performance depends on feed water, pretreatment, design, operation and maintenance.

Binding terms. The only binding specification is Theway's written quotation and order acknowledgement. Supply is under Theway's Terms of Sale, which set out the warranty and limit Theway's liability. Except as stated there, Theway gives no warranty, express or implied, including merchantability or fitness for a particular purpose.

No liability for reliance. To the fullest extent permitted by law, Theway accepts no liability for any loss, damage, injury or cost arising from use of or reliance on this document, or from misuse, incorrect installation, modification or use outside the stated limits, and no liability for indirect, incidental, special or consequential loss.

Your responsibility. The user must confirm that the product is suitable and safe for the intended use, including chemical compatibility, potable-water or food-contact requirements and local regulations, and must have it installed and operated by competent persons.

Replacement products and trade marks. Where this document names another maker's product, the Theway product is built to fit and operate in its place by its published dimensions, connections and ratings. It is not made, approved or endorsed by that maker, and Theway is not connected with it. Fitting it may affect a warranty or service agreement with the original supplier; check before replacing. Brand and model names belong to their owners and are used only for identification.

Changes and versions. Theway may change designs and specifications without notice. This version supersedes all earlier versions; ask for the current version before ordering.

Ownership. © 2026 Theway Membranes. All rights reserved. This document, its drawings and images are Theway's property and are for illustration; supplied products may differ in finish and labelling. They may not be copied, altered, published or passed to third parties without Theway's written permission, except to evaluate Theway products.

Law. Governing law and jurisdiction are as stated in the Terms of Sale. Full terms: www.thewaymembranes.com/post/terms-of-sale and www.thewaymembranes.com/post/product-and-datasheet-disclaimer.

Questions about this document: mail@thewaymembranes.com · +91 44 48502060 · +91 73974 98660. Always ask for the current version before ordering or designing.

Theway Membranes · 29 Yadaval Street, SIDCO Industrial Estate, Ambattur, Chennai 600 098, India
mail@thewaymembranes.com · +91 44 48502060 · www.thewaymembranes.com
Designs are the property of Theway Membranes. Specifications may change without notice. Drawings are not to scale. Issued November 2026.